


ORLEANS TOWEL

With this glass collection we want to reorganize your life space bringing our design and adjusting your habitat. Its elegance and perfection shapes your ideas and makes your building smile. This radiant panel can be installed in each space of your house, from bathroom to living room

- Input voltage 230 Vac
- Protection Class I
- Electrical protection level IP44
- Operative temperature: 60 ÷ 80 °C
- On bathrooms this device can be installed as per zone 2, in compliance with directive IEC 364-7-701:1984
- Cable for electrical connection: 1 m long
- Painted steel structure
- Finish: 4 mm tempered glass
- Certification 
- The company reserves the right to change without notice specifics of the products details declining any responsibility for incorrect data.

For the manual instruction look at page 90

MADE IN ITALY

ORLEANS TOWEL

Installation	Description	Code	Wattage (W)	Colour	Dimension (h*w*d) mm	Weight
VERTICAL	Orleans 350	010410101	350 W	Black	700*500*55	11 kg
	Orleans 500	010420101	500W	Black	1100*500*55	17 kg
	Orleans 750	010430101	750 W	Black	1600*600*55	29 kg
	Orleans 1000	010440101	1000 W	Black	1600*600*55	29 kg
	Orleans 350	010410201	350 W	Brown	700*500*55	11 kg
	Orleans 500	010420201	500W	Brown	1100*500*55	17 kg
	Orleans 750	010430201	750 W	Brown	1600*600*55	29 kg
	Orleans 1000	010440201	1000 W	Brown	1600*600*55	29 kg
HORIZONT.	Orleans 350	010410102	350 W	Black	700*500*55	11 kg
	Orleans 500	010420102	500W	Black	1100*500*55	17 kg
	Orleans 350	010410202	350 W	Brown	700*500*55	11 kg
	Orleans 500	010420202	500W	Brown	1100*500*55	17 kg
ACCESSOR.	Thermoregul.	010000100	Right			0,43 kg
	Thermoregul.	010000200	Left			0,43 kg
	Quadro	010000001			490*40*80	0,57 kg
	Touch	010000002			510*50*80	0,37 kg
	Logic *	010000003			510*30*80	0,70 kg

* Only for Orleans 750 and Orleans 1000



BLACK
RAL 9005



BROWN
RAL 3009



QUADRO



THERMOREGOLATOR



**POSSIBILITY OF
COSTUMAZING WITH
SAND TECHNIQUE OR
COLOUR PRINT**
WITH ESTIMATE



TOUCH



LOGIC