



SILVER SHINE TOWEL

Magnificent ideas, attention to details and the endless Italian appeal: these are C DESIGN keywords. Our company is always paying attention to house heating without forgetting design and materials. Silver shine is a radiant wall panel coated with silver-coloured natural stone, containing a lot of fashionable faint sea reflexes.



- Input voltage 230 Vac
- Protection Class I
- Electrical protection level IP44
- Operative temperature: 60 ÷ 80 °C
- On bathrooms this device can be installed as per zone 2, in compliance with directive IEC 364-7-701:1984
- Cable for electrical connection: 1 m long
- Painted steel structure
- Finish: 2 mm of natural sandtone pre-treated with stain-resistant products
- Certification CE
- Every stone surface of this device has its own peculiar features which depend both on minerals and climate conditions of the place of origin. Accordingly, colours and patterns represented by pictures in the catalogue are merely demonstrative. For that reason, stones which belong to the same class can have different characteristics from each other.
- The company reserves the right to change without notice specifics of the products details declining any responsibility for incorrect data.

For the manual instruction look at page 90

SILVER SHINE TOWEL

Installation	Description	Code	Wattage (W)	Colour	Dimension (h*w*d) mm	Weight	
VERTICAL	Silver Shine 350	010110301	350 W		700*500*55	13 kg	
	Silver Shine 500	010120301	500W		1100*500*55	20 kg	
HORIZON.	Silver Shine 350	010110302	350 W		700*500*55	13 kg	
	Silver Shine 500	010120302	500W		1100*500*55	20 kg	
ACCESSOR.	Thermoregul.	010000100	Right			0,43 kg	
	Tehrmoregul.	010000200	Left			0,43 kg	

THERMOREGULATOR

